


LAYOUT PLAN
NTS

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:
BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.N°. 2006/015089/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za


ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
OVERALL LAYOUT PLAN:
KM 0,000 TO KM 5,843

DRAWING NUMBER	SHEET No.	PAPER SIZE
SMV-LET-PIC-100	SHEET 1 OF 1	A0
SMV PROJECT NUMBER	SCALE	
	AS SHOWN	
CONTRACT No.	DATE	REV No.
	2023.04.18	B





NOTES:

1. DO NOT SCALE OFF THIS DRAWING

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:
BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg N°. 2006/015036/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:


PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
LAYOUT PLAN:
KM 0,000 TO KM 2,000

DRAWING NUMBER: SMV-LET-PIC-101	SHEET No.: SHEET 1 OF 3	PAPER SIZE: A0
SMV PROJECT NUMBER	SCALE: AS SHOWN	
CONTRACT No.	DATE: 2023.04.18	REV No.: B



LAYOUT PLAN
SCALE 1:1000



LAYOUT PLAN
SCALE 1:1000

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:
BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg N°. 2006/015036/07
SUITE 226
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za


ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
LAYOUT PLAN:
KM 2,000 TO KM 4,000

DRAWING NUMBER: SMV-LET-PIC-102	SHEET No.: SHEET 2 OF 3	PAPER SIZE: A0
SMV PROJECT NUMBER:	SCALE: AS SHOWN	
CONTRACT No.:	DATE: 2023.04.18	REV No.: B





MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg N°. 2006/015036/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:

LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:

LAYOUT PLAN:

KM 4,000 TO KM 5,843

DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-103	SHEET 3 OF 3	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	

NOTES


1. ALL ROAD MARKINGS AND SIGN POSTING TO BE IN ACCORDANCE THE SOUTH AFRICAN ROAD TRAFFIC SIGNS MANUAL.
2. EXISTING ROAD MARKING ARE TO BE REMOVED BY SANDBLASTING.
3. ALL TIE-IN COORDINATES TO BE CONFIRMED ON SITE PRIOR TO COMMENCEMENT OF THE WORKS


SETTING OUT COORDINATES

POINT	Y-COORD	X-COORD
L01	-3958.548	2564984.684
L02	-3976.840	2565013.843
L03	-4054.371	2565130.474
L04	-4142.052	2565270.249
L05	-4175.073	2565271.515
L06	-4182.271	2565261.784
L07	-4187.417	2565265.590
L08	-4171.422	2565287.212
L09	-4169.999	2565314.800
L10	-4241.258	2565435.359
L11	-4335.895	2565586.223
R01	-3952.279	2564988.616
R02	-3989.532	2565048.002
R03	-4060.797	2565168.569
R04	-4148.477	2565308.343
R05	-4236.159	2565448.119
R06	-4313.687	2565564.746
R07	-4329.626	2565590.155
C01	-4158.994	2565259.621
C02	-4191.520	2565302.080


ISLAND SETTING OUT COORDS

POINT	Y-COORD	X-COORD
A01	-4144.506	2565279.995
A02	-4163.576	2565284.198
A03	-4157.299	2565292.683
A04	-4152.346	2565292.492
K01	-4150.076	2565283.617
K02	-4160.064	2565285.199
K03	-4160.910	2565286.793
K04	-4156.724	2565292.452
K05	-4153.421	2565292.325
K06	-4148.880	2565285.086





1.5m wide
Walkway
3.20
3.20
Fig 8(c) Mountable
Kerb
DETAIL 'A'
R20.00
STOP
R1
R25.00
5.00
5.50
5.50
3.70
3.70
3.70



NOTE: ALL EXISTING SERVICES WITHIN THE ROAD WORKS WILL BE RELOCATED TO POSITIONS CONFIRMED BY THE ENGINEER ON SITE.

LAYOUT PLAN
SCALE 1:1000

CURVE SETTING OUT DATA


NAME	CH	Y	X	DETAILS
BCC1	340.021	-4 356.926	2 565 031.070	R 2 000.000m
PI1		-4 380.858	2 564 998.718	DA 2°18'20"
ECC1	420.494	-4 403.470	2 564 965.430	TL 40.242m
				AL 80.473m
BCC2	736.790	-4 581.197	2 564 703.788	R 7 500.000m
PI2		-4 605.010	2 564 668.731	DA 0°38'50"
ECC2	821.550	-4 629.218	2 564 633.945	TL 42.381m
				AL 84.760m

SETTING OUT COORDINATES

POINT	Y	X
0	-4154.708	2565304.424
100	-4214.180	2565224.031
200	-4273.652	2565143.638
300	-4333.124	2565063.244
400	-4391.868	2564982.323
500	-4448.144	2564899.662

SETTING OUT COORDINATES

POINT	Y	X
600	-4504.334	2564816.942
700	-4560.524	2564734.221
800	-4616.934	2564651.651
900	-4674.030	2564569.553
1000	-4731.151	2564487.473



SCALES:
Horizontal 1:1000
Vertical 1:100

DATUM 900.000


| | | | |

CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC3	1 019.264	-4 742.155	2 564 471.661	R 500.000m
PI3		-4 763.635	2 564 440.795	DA 8°36'10"
ECC3	1 094.330	-4 789.489	2 564 413.490	TL 37.604m
				AL 75.066m
BCC4	1 135.671	-4 817.913	2 564 383.471	R 200.000m
PI4		-4 834.299	2 564 366.165	DA 13°35'30"
ECC4	1 183.112	-4 846.160	2 564 345.494	TL 23.832m
				AL 47.441m
BCC5	1 308.495	-4 908.559	2 564 236.741	R 15.000m
PI5		-4 915.179	2 564 225.204	DA 83°07'50"
ECC5	1 330.258	-4 927.425	2 564 230.396	TL 13.301m
				AL 21.763m
BCC6	1 400.519	-4 992.112	2 564 257.823	R 150.000m
PI6		-5 031.664	2 564 274.592	DA 31°57'50"
ECC6	1 484.200	-5 074.097	2 564 267.881	TL 42.960m
				AL 83.681m


CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC7	1 559.351	-5 148.325	2 564 256.141	R 250.000m
PI7		-5 171.273	2 564 252.512	DA 10°37'10"
ECC7	1 605.683	-5 194.496	2 564 253.173	TL 23.232m
				AL 46.332m
BCC8	1 748.437	-5 337.191	2 564 257.236	R 30.000m
PI8		-5 355.018	2 564 257.743	DA 61°27'30"
ECC8	1 780.616	-5 363.981	2 564 242.326	TL 17.833m
				AL 32.180m
BCC9	1 840.472	-5 394.065	2 564 190.580	R 60.000m
PI9		-5 411.407	2 564 160.750	DA 59°48'10"
ECC9	1 903.099	-5 445.911	2 564 160.736	TL 34.504m
				AL 62.627m

SETTING OUT COORDINATES		
POINT	Y	X
1000	-4731.151	2564487.473
1100	-4793.388	2564409.373
1200	-4854.564	2564330.846
1300	-4904.331	2564244.109
1400	-4991.634	2564257.620
1500	-5089.703	2564265.413

SETTING OUT COORDINATES		
POINT	Y	X
1600	-5188.814	2564253.076
1700	-5288.774	2564255.857
1800	-5373.723	2564225.569
1900	-5442.814	2564160.817
2000	-5542.812	2564160.696




LAYOUT PLAN
SCALE 1:1000



| | | | |

SETTING OUT COORDINATES		
POINT	Y	X
2000	-5542.812	2564160.696
2100	-5642.812	2564160.655
2200	-5742.812	2564160.614
2300	-5842.812	2564160.573
2400	-5942.812	2564160.532
2500	-6042.812	2564160.491


SETTING OUT COORDINATES		
POINT	Y	X
2600	-6142.812	2564160.450
2700	-6242.812	2564160.409
2800	-6342.812	2564160.368
2900	-6442.812	2564160.327
3000	-6542.812	2564160.286



Note:
1. Existing Portal Culvert to be Retained (Do not Demolish).
2. Clean the Existing Culverts Barrels including Inlets and Outlets.
3. Construct New Guard Rails on either side along the Culvert.
4. Add 4No. Culvert Markers.
5. The Culvert Headwalls to be increased to 200mm (min) above the Finished Road Level

NOTE: ALL EXISTING SERVICES WITHIN THE ROAD WORKS WILL BE RELOCATED TO POSITIONS CONFIRMED BY THE ENGINEER ON SITE.

LAYOUT PLAN
SCALE 1:1000



Note:
1. Existing Portal Culvert to be Retained (Do not Demolish).
2. Clean the Existing Culverts Barrels including Inlets and Outlets.
3. Construct New Guard Railson either side along the Culvert.
4. Add 4No. Culvert Markers.

SCALES:
Horizontal 1:1000
Vertical 1:100

DATUM 895.000


| | | |

CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC10 PI10 ECC10	3 063.098	-6 605.910 -6 666.775 -6 727.443	2 564 160.261 2 564 160.236 2 564 165.142	R 1 500.000m DA 4°38'50" TL 60.865m AL 121.664m
BCC11 PI11 ECC11	3 353.622 3 417.816	-6 895.753 -6 928.089 -6 957.477	2 564 178.754 2 564 181.370 2 564 195.109	R 180.000m DA 20°26'00" TL 32.442m AL 64.194m
BCC12 PI12 ECC12	3 579.708 3 646.638	-7 104.133 -7 134.961 -7 156.552	2 564 263.675 2 564 278.088 2 564 304.393	R 150.000m DA 25°33'50" TL 34.031m AL 66.930m


CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC13 PI13 ECC13	3 682.917 3 863.967	-7 179.568 -7 243.124 -7 341.657	2 564 332.437 2 564 409.872 2 564 391.792	R 170.000m DA 61°01'10" TL 100.178m AL 181.050m
BCC14 PI14 ECC14	3 906.815 3 982.515	-7 383.801 -7 421.066 -7 458.850	2 564 384.059 2 564 377.222 2 564 374.446	R 700.000m DA 6°11'50" TL 37.886m AL 75.699m
BCC15 PI15 ECC15	4 028.220 4 063.072	-7 504.433 -7 525.308 -7 530.487	2 564 371.097 2 564 369.564 2 564 389.844	R 25.000m DA 79°52'30" TL 20.931m AL 34.852m

SETTING OUT COORDINATES		
POINT	Y	X
3000	-6542.812	2564160.286
3100	-6642.808	2564160.699
3200	-6742.631	2564166.371
3300	-6842.306	2564174.432
3400	-6940.991	2564188.374
3500	-7031.927	2564229.916

SETTING OUT COORDINATES		
POINT	Y	X
3600	-7121.879	2564273.484
3700	-7191.051	2564345.075
3800	-7278.068	2564391.368
3900	-7377.098	2564385.289
4000	-7476.289	2564373.165
4100	-7539.625	2564425.623



LAYOUT PLAN
SCALE 1:1000




| | | | |

CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC15 PI15 ECC15	4 028.220 4 063.072	-7 504.433 -7 525.308 -7 530.487	2 564 371.097 2 564 369.564 2 564 389.844	R 25.000m DA 79°52'30" TL 20.931m AL 34.852m
BCC16 PI16 ECC16	4 150.144 4 221.879	-7 552.034 -7 561.006 -7 581.738	2 564 474.208 2 564 509.337 2 564 539.081	R 200.000m DA 20°33'00" TL 36.257m AL 71.734m
BCC17 PI17 ECC17	4 291.054 4 349.504	-7 621.294 -7 638.154 -7 646.416	2 564 595.831 2 564 620.015 2 564 648.322	R 180.000m DA 18°36'20" TL 29.485m AL 58.450m


CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC18 PI18 ECC18	4 427.344 4 777.995	-7 668.227 -7 723.833 -7 570.270	2 564 723.044 2 564 913.545 2 565 039.248	R 300.000m DA 66°58'10" TL 198.451m AL 350.651m
BCC19 PI19 ECC19	4 836.919 4 972.265	-7 524.673 -7 446.181 -7 534.102	2 565 076.571 2 565 140.823 2 565 191.411	R 70.000m DA 110°46'50" TL 101.436m AL 135.345m
BCC20 PI20 ECC20	4 990.916 5 050.573	-7 550.268 -7 576.391 -7 606.089	2 565 200.713 2 565 215.744 2 565 220.878	R 170.000m DA 20°06'20" TL 30.139m AL 59.658m

SETTING OUT COORDINATES		
POINT	Y	X
4000	-7476.289	2564373.165
4100	-7539.625	2564425.623
4200	-7570.233	2564520.484
4300	-7626.225	2564603.294
4400	-7660.565	2564696.796
4500	-7679.982	2564794.564

SETTING OUT COORDINATES		
POINT	Y	X
4600	-7667.587	2564893.326
4700	-7623.559	2564982.597
4800	-7553.242	2565053.186
4900	-7499.022	2565131.880
5000	-7558.259	2565205.031
5100	-7654.793	2565229.299



LAYOUT PLAN
SCALE 1:1000



MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT: BLOUBERG MUNICIPALITY

CONSULTANT: SEBEGO, MALOKA & VILJOEN CIVIL ENGINEERS (PTY) LTD
Reg N°. 2006/015036/07
SUITE 228
POSTNET X93307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME: **LETHALENG TO PICKUM ROAD UPGRADING**


DRAWING TITLE: **LAYOUT AND LONGITUDINAL SECTION: KM 4,000 TO KM 5,000**

DRAWING NUMBER	SMV-LET-PIC-205	SHEET No.	SHEET 5 OF 6
PAPER SIZE	A0		
SMV PROJECT NUMBER		SCALE	AS SHOWN
CONTRACT No.		DATE	2023.04.18
REV No.	B		


CURVE SETTING OUT DATA				
NAME	CH	Y	X	DETAILS
BCC20 PI20 ECC20	4 990.916 5 050.573	-7 550.268 -7 576.391 -7 606.089	2 565 200.713 2 565 215.744 2 565 220.878	R 170.000m DA 20°06'20" TL 30.139m AL 59.658m
BCC21 PI21 ECC21	5 151.508 5 254.094	-7 705.549 -7 756.312 -7 803.778	2 565 238.074 2 565 246.850 2 565 266.872	R 450.000m DA 13°03'40" TL 51.516m AL 102.586m
BCC22 PI22 ECC22	5 336.712 5 442.906	-7 879.901 -7 928.831 -7 978.594	2 565 298.982 2 565 319.621 2 565 338.164	R 2 500.000m DA 2°26'00" TL 53.105m AL 106.194m
BCC23 PI23 ECC23	5 514.573 5 567.785	-8 045.750 -8 070.684 -8 095.273	2 565 363.188 2 565 372.479 2 565 382.648	R 1 500.000m DA 2°02'00" TL 26.609m AL 53.212m

SETTING OUT COORDINATES		
POINT	Y	X
5000	-7558.259	2565205.031
5100	-7654.793	2565229.299
5200	-7752.794	2565248.891
5300	-7846.075	2565284.713
5400	-7938.519	2565322.838

SETTING OUT COORDINATES		
POINT	Y	X
5500	-8032.094	2565358.099
5600	-8125.042	2565394.960
5700	-8217.450	2565433.179
5800	-8309.859	2565471.398
5843	-8349.697	2565487.874




LAYOUT PLAN
SCALE 1:1000




SCALES:
Horizontal 1:1000
Vertical 1:100

DATUM 910.000


| | | | |



CLASS B BEDDING ON SOFT MATERIAL (SINGLE PIPE)




CLASS B BEDDING ON ROCK (SINGLE PIPE)




CLASS A BEDDING


OD - OUTSIDE DIAMETER OF PIPE
ID - INSIDE DIAMETER OF PIPE



CLASS B BEDDING ON SOFT MATERIAL



CLASS B BEDDING ON ROCK



CLASS A BEDDING

NOTES

1 .01 ALL CONCRETE PIPE CULVERTS SHALL COMPLY WITH THE REQUIREMENTS OF SANS 677.


1 .02 ROAD DRAINAGE PIPES

- THE PIPE CLASS IS DETERMINED FROM THE WEIGHT OF THE PRISM OF FILL ABOVE THE PIPE CULVERT PLUS THE SNABC LOADINGS IN ACCORDANCE WITH TMH 7 (PARTS 1&2) "CODE OF PRACTICE FOR THE DESIGN OF HIGHWAY BRIDGES AND CULVERTS IN SOUTH AFRICA" AND STATED IN THE DRAINAGE SCHEDULE (TO BE ISSUED)

- THE MAXIMUM WHEEL LOAD ALLOWED ON THE PIPE IS 90KN WITH A MINIMUM FILL OF 150mm ON TOP OF THE PIPE FOR BOTH BEDDING CONDITIONS AND ALL PIPE DIAMETERS AS SHOWN.

1 .03 CONCRETE BACKFILL CLASS 20/19 MPa.

Pipe Ø (mm)	Dim ('x') (mm)
450 - 600	150
750 - 900	300
900 - 1200	500



CLASS A BEDDING

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg N°: 2004/018566/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
STORMWATER DRAINAGE
PIPE CULVERT - BEDDING DETAILS

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-403	SHEET 1 OF 1
SMV PROJECT NUMBER	SCALE
	AS SHOWN
CONTRACT No.	DATE / REV No.
	2023.04.24 / B



ELEVATION A
1 : 25

NOTE:
1. SPACING (S) BETWEEN PIPES TO BE 100mm ONLY IF SOILCRETE BACKFILLING IS USED.
2. N = NUMBER OF PIPES.




PLAN A
1 : 25


MULTIPLE PIPE CULVERT

NOTE:
1. SPACING (S) BETWEEN PIPES TO BE 100mm ONLY IF SOILCRETE BACKFILLING IS USED.
2. N = NUMBER OF PIPES.
3. EROSION PROTECTION AND ENERGY BREAKING BLOCKS FOR MULTIPLE PIPE CULVERT SIMILAR TO SINGLE PIPE CULVERT.

INSIDE DIA. PIPE (D)	T (mm)	S (mm)
750	150	375
900	175	450
1050	200	500
1200	200	500




ELEVATION B
1 : 20




PLAN B
1 : 25

TYPE 1 INLET




SECTION C
1 : 20

(INLET)




SECTION G
1 : 20

(OUTLET)




PLAN B
1 : 25

TYPE 1 AND TYPE 1A OUTLET



SECTION F
1 : 20



SECTION E
1 : 20

NOTES:

CONSTRUCTION

1. ALL EXPOSED CORNERS SHALL BE CHAMFERED 25 x 25
2. CONCRETE COVER TO REINFORCEMENT:-
   FLOOR SLAB & FOOTINGS = 50mm
   WINGWALLS = 40mm
3. CONCRETE FINISH:
   CONCEALED SURFACES = F1
   EXPOSED SURFACES = F2
4. POLYETHYLENE SHEET 0.15mm THICK SHALL BE PLACED UNDER ALL WINGWALL FOOTINGS AND INLET SLAB
5. THIS DRAWING TO BE READ IN CONJUNCTION WITH THE COLTO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE WORKS FOR STATE ROAD AUTHORITIES AS AMENDED TO DATE
6. THE UPPER LEVEL OF THE FILL ALWAYS PASSES THROUGH A POINT 100mm BELOW THE TOP OF THE HEAD WALL
7. THE MAXIMUM SLOPE OF EARTHWORKS SURROUNDING A CULVERT INLET OR OUTLET SHALL BE 1 : 2

MATERIAL SPECIFICATION:

1. INLET/OUTLET CONCRETE SLABS AND WINGWALLS - CLASS 20/19
   CHARACTERISTIC STRENGTH 20 MPa
   YOUNG'S MODULUS 28 000 MPa
2. REINFORCEMENT (SABS 920 - 1985)
   YIELD STRENGTH TYPE:
   MILD STEEL BARS 250 MPa
   HIGH TENSILE STEEL BARS 450 MPa
   WELDED STEEL FABRIC 450 MPa

DESIGN METHOD:

1. LIMIT STATE DESIGN ACCORDING TO TMH7 PART 3 AS AMENDED 1989
2. INLET AND OUTLET STRUCTURES ARE DESIGNED FOR LOADING SPECIFIED IN TMH7 PART 1 AND 2 AS AMENDED 1988 "CODE OF PRACTICE FOR THE DESIGN OF HIGHWAY BRIDGES AND CULVERTS IN S.A."
3. TYPE OF REINFORCEMENT AND SPACING ARE SHOWN ON THE DRAWINGS. THE CONTRACTOR MUST SUBMIT WORKING DRAWINGS AND BENDING SCHEDULES FOR APPROVAL.

FOUNDING MATERIAL:

1. MAX. CALCULATED GROUND PRESSURE - 100kPa
2. FOUNDING LEVEL TO BE APPROVED BY THE PROJECT MANAGER.

HYDRAULIC INFORMATION:

1. SEE DRAINAGE SCHEDULE FOR FLOOD LEVELS, OUTLET TYPE AND HYDRAULIC DATA FOR EACH CULVERT.

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SEBEGO, MALOKA & VILJOEN (PTY) LTD CIVIL ENGINEERS
Reg N°. 2006/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:


PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
STORMWATER INLET/OUTLET CONCRETE DETAILS FOR PIPE CULVERTS @ 90° TO THE ROAD:
(Ø750mm TO Ø1200mm)


DRAWING NUMBER	SHEET No.
SMV-LET-PIC-404	SHEET 1 OF 1
SMV PROJECT NUMBER	SCALE
	AS SHOWN
CONTRACT No.	DATE / REV No.
	2023.04.24 / B



ELEVATION A
1 : 25




ELEVATION B
1 : 20



SECTION C
1 : 20


(INLET)



SECTION F
1 : 20

SECTION D
1 : 20


(OUTLET)



PLAN A
1 : 25

TYPICAL INLET AND OUTLET


NOTE:
1. SPACING (S) BETWEEN PIPES TO BE 100mm ONLY IF SOILCRETE BACKFILLING IS USED.
2. N = NUMBER OF PIPES.
3. EROSION PROTECTION AND ENERGY BREAKING BLOCKS FOR MULTIPLE PIPE CULVERT SIMILAR TO SINGLE PIPE CULVERT. (SEE SINGLE PIPE CULVERT)



PLAN B
1 : 25


TYPE 1 INLET

INSIDE DIA. PIPE (D)	T (mm)	S (mm)
750	150	375
900	175	450
1050	200	500
1200	200	500



PLAN B
1 : 25

TYPE 1 AND TYPE 1A OUTLET



SECTION G
1 : 20

NOTES:

CONSTRUCTION

1. ALL EXPOSED CORNERS SHALL BE CHAMFERED 25 x 25
2. CONCRETE COVER TO REINFORCEMENT:-
   FLOOR SLAB & FOOTINGS = 50mm
   WINGWALLS = 40mm
3. CONCRETE FINISH:
   CONCEALED SURFACES = F1
   EXPOSED SURFACES = F2
4. POLYETHYLENE SHEET 0.15mm THICK SHALL BE PLACED UNDER ALL WINGWALL FOOTINGS AND INLET SLAB
5. THIS DRAWING TO BE READ IN CONJUNCTION WITH THE COLTO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE WORKS FOR STATE ROAD AUTHORITIES AS AMENDED TO DATE
6. THE UPPER LEVEL OF THE FILL ALWAYS PASSES THROUGH A POINT 100mm BELOW THE TOP OF THE HEAD WALL
7. THE MAXIMUM SLOPE OF EARTHWORKS SURROUNDING A CULVERT INLET OR OUTLET SHALL BE 1 : 2

MATERIAL SPECIFICATION:

1. INLET/OUTLET CONCRETE SLABS AND WINGWALLS - CLASS 20/19
   CHARACTERISTIC STRENGTH 20 MPa
   YOUNG'S MODULUS 28 000 MPa
2. REINFORCEMENT (SABS 920 - 1985)
   YIELD STRENGTH TYPE:
   MILD STEEL BARS 250 MPa
   HIGH TENSILE STEEL BARS 450 MPa
   WELDED STEEL FABRIC 450 MPa

DESIGN METHOD:

1. LIMIT STATE DESIGN ACCORDING TO TMH7 PART 3 AS AMENDED 1989
2. INLET AND OUTLET STRUCTURES ARE DESIGNED FOR LOADING SPECIFIED IN TMH7 PART 1 AND 2 AS AMENDED 1988 "CODE OF PRACTICE FOR THE DESIGN OF HIGHWAY BRIDGES AND CULVERTS IN S.A."
3. TYPE OF REINFORCEMENT AND SPACING ARE SHOWN ON THE DRAWINGS. THE CONTRACTOR MUST SUBMIT WORKING DRAWINGS AND BENDING SCHEDULES FOR APPROVAL.

FOUNDING MATERIAL:

1. MAX. CALCULATED GROUND PRESSURE - 100kPa
2. FOUNDING LEVEL TO BE APPROVED BY THE PROJECT MANAGER.

HYDRAULIC INFORMATION:

1. SEE DRAINAGE SCHEDULE FOR FLOOD LEVELS, OUTLET TYPE AND HYDRAULIC DATA FOR EACH CULVERT.

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2004/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0700
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
STORMWATER INLET/OUTLET REINFORCEMENT DETAILS FOR SKEW PIPE CULVERTS AND @ 90° TO THE ROAD:
(Ø750mm TO Ø1200mm PIPES)

DRAWING NUMBER	SMV-LET-PIC-405
SHEET No.	SHEET 1 OF 1
SMV PROJECT NUMBER	
SCALE	AS SHOWN
CONTRACT No.	
DATE	2023.04.24
REV No.	B




NOTE:
1. STEEL IN WINGWALL AND STARTER BARS NOT SHOWN FOR CLARITY
2. SKEW PIPE CULVERTS SIMILAR
3. COVER TO REINFORCEMENT 40mm

ELEVATION C
1 : 20




NOTE:
1. STEEL IN WINGWALL AND STARTER BARS NOT SHOWN FOR CLARITY
2. SKEW PIPE CULVERTS SIMILAR
3. COVER TO REINFORCEMENT 40mm

ELEVATION F
1 : 20




NOTE:
1. WELDED STEEL FABRIC MUST COVER TOTAL AREA OF SLAB
2. SKEW PIPE CULVERTS SIMILAR

PLAN A
1 : 20




SECTION M
1 : 10




NOTE:
REINFORCEMENT IN SLAB NOT SHOWN FOR CLARITY


TYPICAL WINGWALL ELEVATION
1:20



SECTION H
1 : 20




SECTION P
1 : 10




SECTION K
1 : 20

INSIDE DIA. PIPE (D)	T	WELDED FABRIC REF No	
		TYPE A	TYPE B
450	150	245	245
600	150	245	245
750	150	395	245
900	175	395	245



SECTION S
1 : 10



NOTE:
COVER TO REINFORCEMENT 40mm

SECTION L
1 : 20

LEGEND


EF = EACH FACE
OF = OUTSIDE FACE
IF = INSIDE FACE

20MPa CONCRETE - BAR LAP LENGTHS

BAR DIA.	10	12
LAP LENGTH	550	660

20MPa CONCRETE - MESH LAP LENGTHS

WELDED STEEL FABRIC REF. No.	245	311	395	500	617
MIN LAP LENGTH	450	500	600	650	750



NOTE:
1. WELDED STEEL FABRIC MUST COVER TOTAL AREA OF SLAB
2. SKEW PIPE CULVERTS SIMILAR

PLAN B
1 : 20

FLOOR SLAB - SINGLE PIPE CULVERT

FLOOR SLAB - MULTIPLE PIPE CULVERT

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SEBEGO, MALOKA & VILJOEN (PTY) LTD CIVIL ENGINEERS
Reg.N°. 2004/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
STORMWATER INLET/OUTLET REINFORCEMENT DETAILS FOR SKEW PIPE CULVERTS AND @ 90° TO THE ROAD:
(Ø450mm TO Ø900mm PIPES)

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-406	SHEET 1 OF 1
SMV PROJECT NUMBER	SCALE
	AS SHOWN
CONTRACT No.	DATE / REV No.
	2023.04.24 / B




NOTE:
1. STEEL IN WINGWALL AND STARTER BARS NOT SHOWN FOR CLARITY
2. SKEW PIPE CULVERTS SIMILAR
3. COVER TO REINFORCEMENT 40mm

ELEVATION C
1 : 20



ELEVATION F
1 : 20


NOTE:
1. STEEL IN WINGWALL AND STARTER BARS NOT SHOWN FOR CLARITY
2. SKEW PIPE CULVERTS SIMILAR
3. COVER TO REINFORCEMENT 40mm




PLAN A
1 : 20

NOTE:
1. WELDED STEEL FABRIC MUST COVER TOTAL AREA OF SLAB
2. SKEW PIPE CULVERTS SIMILAR

FLOOR SLAB - MULTIPLE PIPE CULVERT




SECTION M
1 : 10




NOTE:
REINFORCEMENT IN SLAB NOT SHOWN FOR CLARITY

TYPICAL WINGWALL ELEVATION
1:20




NOTE:
COVER TO REINFORCEMENT 40mm

SECTION H
1 : 20




SECTION P
1 : 10




NOTE:
COVER TO REINFORCEMENT 40mm

SECTION K
1 : 20

INSIDE DIA. PIPE (D)	T	WELDED FABRIC REF No			
		TYPE A	TYPE B	TYPE C	TYPE D
1050	200	500	311	245	245
1200	200	617	311	245	245



SECTION S
1 : 10



NOTE:
COVER TO REINFORCEMENT 40mm

SECTION L
1 : 20

LEGEND


EF = EACH FACE
OF = OUTSIDE FACE
IF = INSIDE FACE

20MPa CONCRETE - BAR LAP LENGTHS

BAR DIA.	10	12
LAP LENGTH	550	660

20MPa CONCRETE - MESH LAP LENGTHS

WELDED STEEL FABRIC REF. No.	245	311	395	500	617
MIN LAP LENGTH	450	500	600	650	750



NOTE:
1. WELDED STEEL FABRIC MUST COVER TOTAL AREA OF SLAB
2. SKEW PIPE CULVERTS SIMILAR

PLAN PLN
SCALE REF

FLOOR SLAB - SINGLE PIPE CULVERT

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.N° 2006/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:


PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
STORMWATER INLET/OUTLET REINFORCEMENT DETAILS FOR SKEW PIPE CULVERTS AND @ 90° TO THE ROAD:
(Ø1050mm TO Ø1200mm PIPES)

DRAWING NUMBER	SMV-LET-PIC-407
SHEET No.	SHEET 1 OF 1
SMV PROJECT NUMBER	
SCALE	AS SHOWN
CONTRACT No.	
DATE	2023.04.24
REV No.	B




PLAN



SECTION A - A


STANDARD PROPERTY ACCESS CULVERT

(ONLY WHERE INSTRUCTED BY THE ENGINEER ON STE)




* NOTE: K.I's AT LOW POINTS TO HAVE 2 000 TRANSITIONS BOTH SIDES

TYPICAL PLAN
SCALE 1 : 25




SECTION A-A
SCALE 1 : 25




SECTION B-B
SCALE 1 : 25

NOTE:
A) 450 - 525 dia pipes
B) 600 dia pipe
C) 750 dia pipe
D) 825 - 1 350 dia pipes




NOTE:
All exposed surfaces of mild steel to be thoroughly cleaned and painted with 1 coat of metal primer, 1 coat of undercoat and 2 coats of red enamel (all to approval)

DETAIL 1 SCALE 1:10
ANGLE IRON SUPPORTS



SECTION C-C
SCALE 1 : 25



DETAIL 2
SCALE 1:5

NOTES

1. All exposed steelwork to receive two coats of epoxy tar.
2. Top of precast concrete cover slabs to be clearly marked.
3. Finishes a) top of precast concrete cover slab wood float.
   b) benching - granolithic finish.
   c) cement plaster to inside walls 10mm thick.
4. Concrete for bases and cover slabs to be class 25/19 and for blinding to be 15/19.
5. Cover to reinforcement = 40mm
6. All brickwork to be constructed from best quality engineering bricks. to S.A.B.S.227.

STANDARD KERB INLETS / STORMWATER DRAINAGE CATCHPITS

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
CIVIL ENGINEERS (PTY)LTD
SEBEGO, MALOKA & VILJOEN
Reg N°. 2004/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
STANDARD PROPERTY ACCESS CULVERT & TYPICAL STORMWATER DETAILS

DRAWING NUMBER	SMV-LET-PIC-408
SHEET No.	SHEET 1 OF 1
SMV PROJECT NUMBER	
SCALE	AS SHOWN
CONTRACT No.	
DATE	2023.04.24
REV No.	B



TYPICAL SECTION OF SUBSOIL DRAIN WITH SYNTHETIC FIBRE FILTER FABRIC

(8 sectors of 45°) with perforations in 6 of the 8 as indicated. Position of perforations (HDPE-pipes) (5c) (can be used for both polyethylene linings or synthetic fibre filter fabric)



POSITION OF PERFORATIONS IN SUBSOIL DRAINAGE PIPES

(WHEN USED WITH SYNTHETIC FIBRE FILTER FABRIC)

CLEANING EYE IN SUBSOIL DRAIN

NO.	DESCRIPTION
1	This dimension may be reduced to a minimum of pipe diameter + 200mm provided that the cross-sectional area is adequate (see subclause 2101(b) of the standard specifications).
2	Impermeable backfill material (min 150mm thick) taken to top of water bearing layer in cases where no concrete side drain is provided.
3	Filter sand of approved source and grade.
4a 4b	Filter stone: fine or coarse grade as required, (see subclause 2104(a)(ii)of the standard specifications).
5a 5b 5c	Perforated / slotted subsoil drainage pipes. (Position of perforations indicated).
6a	Polyethylene 0.15mm thickness.
6b	Synthetic fibre filter fabric with 200mm overlap (grade 2 or approved equivalent).
7	Level to which surrounding area is to be drained.
8	Internal diameter: 110mm or 150mm.
9	Water bearing strata.

NOTES:

1. All criteria assumes that filter sand and filter stone are continuously graded from coarse.
2. Use the envelope curves for the water bearing strata, filter sand and filter stone gradings and apply to most critical combinations.
3. If required by the Engineer, subsoil drainage must also be provided on the inside of benching, where used.
4. Where subsoil drainage is installed in solid rock the polyethylene lining may be omitted.
5. Type A outlet preferably to be used where the natural ground levels allow it. Outlets may also be combined with culvert in or outlets.
6. All concrete shall be class 20/19.
7. Spacing of cleaning eyes to be as follows:
   a) 100mm max. on straight sections,
   b) at all bends,
   c) or as directed by the Engineer.
8. Transverse subsoil drainage to be provided at all cut to fill transitions.
9. Plate with the inscription "cleaning eye for subsoil drain", stamped on to be affixed to concrete cover.
10. Letter size on plate: 10mm Series C, capital letters.
11. Synthetic fibre filter fabric to be replaced with polyethylene lining in the following instances;
    a) where the surrounding soil is very permious,
    b) where the surrounding soil has a high fines content which could lead to clogging of filter fabrics.
12. Steel plate to be fixed to top of fenceline opposite the subsoil outlet stucture.
13. Background: Matt-white
    Text : din A, Matt-black

FILTER CRITERIA:

A. "Dx" is the size of sieve through which x% of the filter material will pass.
D_{50}(GF) = average size of the openings of the synthetic fibre filter fabric.

B. FILTER SAND (FS) IN RELATION TO WATER BEARING STRATA (WS).

1. For D_{85}(WS) > 0.05mm;
   (a) to prevent blocking of filter sand:
   D_{15}(FS) < 5 x D_{85}(WS)
   D_{50}(FS) < 25 x D_{50}(WS)
   (b) for permeability of filter sand:
   D_{15}(FS) > 5 x D_{15}(WS)

2. For D_{85}(WS) < 0.05mm:
   (a) to prevent blocking of filter sand:
   D_{15}(FS) < 0.25mm
   D_{85}(FS) > 0.075mm
   (b) for permeability requirements not necessary.

C. FILTER STONE (FSN) IN RELATION TO FILTER SAND (FS).

   (a) To prevent blocking of filter stone:
   D_{15}(FSN) < 5 x D_{85}(FS)
   D_{50}(FSN) < 25 x D_{50}(FS)
   (b) Permeability: filter stone must be coarser than sand all percentages.

D. FILTER STONE (FSN) IN RELATION TO PERFORATIONS IN PIPES.

   (a) To prevent blocking of perforations in pipes:
   D_{85}(FSN) > 1.2 x Diameter of round perforations
   D_{85}(FSN) > 1.2 x Width of slots

E. SYNTHETIC FIBRE FILTER FABRIC (SF) IN RELATION TO FILTER SAND (FS)

   (a) To prevent clogging of synthetic fibre filter fabric:
   O_{50}(SF) < D_{85}(FS)
   (b) For permeability of synthetic fibre filter fabric:
   O_{50}(SF) > D_{15}(FS)

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:
1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg Nº. 2006/018586/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
SUBSURFACE DRAINAGE DETAILS

DRAWING NUMBER	SMV-LET-PIC-409
SHEET No.	SHEET 1 OF 1
SMV PROJECT NUMBER	
SCALE	AS SHOWN
CONTRACT No.	
DATE	2023.04.24
REV No.	B




RURAL LONGITUDINAL LINE TYPES


NOTES: (RURAL LONGITUDINAL LINE TYPES)

1. DIRECTION OF TRAFFIC MOVEMENT WITH RESPECT TO LINE MARKING INDICATED THUS OR .
2. PAINTED ISLAND MARKINGS SHALL BE USED AS A STANDARD DIVIDING MARKING ON ALL 4-LANE 2-WAY ROADWAYS. (SEE URBAN LONGITUDINAL LINE TYPES).
3. A NO OVERTAKING LINE MAY BE USED TO REPLACE A DIVIDING LINE MARKING ON MINOR ROADS OR TO MATCH PROVINCIAL ROAD MARKING POLICY ON AN INTERSECTING ROADWAY AS APPROPRIATE. A NO OVERTAKING LINE MAY BE USED IN COMBINATION WITH A LANE LINE. (NORMALLY ON A FREEWAY CARRIAGEWAY).
4. A LEFT EDGE LINE MARKING SHALL NOT EXTEND ACROSS THE POINT OF DEPARTURE FROM A THROUGH PORTION OF ROADWAY.
5. A RIGHT EDGE LINE MARKING IS ONLY REQUIRED TO DEMARCATE AN UNKERBED MEDIAN. (A MEDIAN GUARDRAIL OR CONCRETE SEPARATOE BARRIER DOES NOT CONSTITUTE A KERBED MEDIAN.)
6. THE DIVIDING LINE MARKING REPLACES THE PREVIOUS "CENTRE LINE" MARKING AND SHALL ONLY BE USED BETWEEN LANES CARRYING OPPOSING TRAFFIC FLOWS WHERE OVERTAKING IS PERMITTED.
7. A CONTINUITY LINE MAY BE SPECIFIED IN ONE OF THREE DENSITIES 1. REDUCED, 2. STANDARD OR 3. EXTRA. A CONTINUITY LINE MAY BE USED TO DEFINE THE LIMIT OF THE THROUGH PORTION OF A ROADWAY, EITHER AT A HIGH SPEED EXIT (OFF-RAMP OR SLIP ROAD), A DEDICATED EXIT LANE ON FREEWAY, OR AT-GRADE SLIP ROAD GORE AREA.
9. A LANE LINE, CONTINUITY LINE OR CHANNELIZING LINE SHALL NOT BE USED BETWEEN OPPOSING TRAFFIC MOVEMENTS.
10. THE WIDTHS OF LINES SHOWN ARE RECOMMENDATIONS ONLY (SEE LONGITUDINAL LINE COMBINATIONS).

LEGEND:
R = RED
W = WHITE
Y = YELLOW




DETAIL "A2"



NOTES: (LONGITUDINAL LINE COMBINATIONS)

1. DIRECTION OF TRAFFIC MOVEMENT WITH RESPECT TO THE MARKING INDICATED THUS OR .
2. FOR FULL LONGITUDINAL DIMENSIONS OF COMPONENT MARKINGS SEE RURAL AND URBAN LONGITUDINAL LINE TYPES.
3. COMBINATION MARKINGS 1 TO 4 ARE FOR TWO WAY TRAFFIC AND ARE APPLICABLE TO NATIONALNON-FREEWAY ROUTES WHICH INTERSECT FREEWAYS.
4. COMBINATION MARKING 5 SHALL BE USED TO INDICATE THE DIVISIONS BETWEEN THE THROUGH ROADWAY AND ANY EXCLUSIVE EXIT/ TURN LANES. WHEREVER POSSIBLE A CONTINUITY LINE SHOULD LEAD TO, OR TERMINATE IN A CHANNELIZING LINE WHICH MAY BE SHORT. RECOMMENDED MINIMUM LENGTH IS 12m FOR RURAL AND 9m FOR URBAN APPLICATIONS.
5. FOR MARKINGS 1 TO 4 ROADSTUDS SHOULD BE LOCATED ON CENTRELINE OF THE DIVIDING LINE (OR SINGLE NO OVERTAKING LINE MARKING 4).
6. WHERE POSSIBLE THE LENGTH OF CHANNELIZING MARKING SHOULD BE ADJUSTED SO THAT THE CONTINUITY LINE ROADSTUDS MATCH OTHER ROADSTUDS ON CROSS SECTION AND FALL IN THE CENTRE OF A GAP IN THE CONTINUITY LINE.
7. DIMENSIONS FOR URBAN APPLICATIONS ARE INDICATED IN BRACKETS.
8. ROADSTUDS ON THE SINGLE NO OVERTAKING LINE IN MARKING 4 MAY BE COVERED DURING LINE MARKING OR PLACED AS INDICATED IN DETAIL "A2"..


LONGITUDINAL LINE COMBINATIONS



URBAN LONGITUDINAL LINE TYPES

NOTES: (URBAN LONGITUDINAL LINE TYPES)


1. DIRECTION OF TRAFFIC MOVEMENT WITH RESPECT TO LINE MARKING INDICATED THUS OR .
2. A NO CROSSING LINE MAY BE USED AS A FORM OF DIVIDING LINE MARKING, IN PLACE OF A NO OVERTAKING LINE, TO PROHIBIT ACCESS TO OR FROM PROPERTIES AT THE SIDE OF AN URBAN ROAD. A PAINTED ISLAND MAY BE USED AS AN ALTERNATIVE MARKING FOR THIS PURPOSE.
3. A NO OVERTAKING LINE MAY BE USED TO REPLACE A DIVIDING LINE MARKING TO PROHIBIT OVERTAKING IN THE PATH OF ON-COMING TRAFFIC. A NO OVERTAKING LINE MAY BE USED IN COMBINATION WITH A LANE LINE.
4. LEFT EDGE LINE MARKING SHALL NOT BE EXTENDED ACROSS THE POINT OF DEPARTURE FROM A THROUGH PORTION OF ROADWAY.
5. A RIGHT EDGE LINE MARKING IS ONLY REQUIRED TO DEMARCATE AN UNKERBED MEDIAN. (A MEDIAN GUARDRAIL OR CONCRETE SEPARATOR BARRIER DOES NOT CONSTITUTE A KERBED MEDIAN.)
6. THE DIVIDING LINE MARKING REPLACES THE PREVIOUS "CENTRE LINE" MARKING AND SHALL ONLY BE USED BETWEEN LANES CARRYING OPPOSING TRAFFIC FLOWS WHEN OVERTAKING IS PERMITTED.
7. A CONTINUITY LINE MAY BE SPECIFIED IN ONE OF THREE DENSITIES 1. REDUCED, 2. STANDARD OR 3. EXTRA. THROUGH PORTION OF A ROADWAY EITHER AT A HIGH SPEED EXIT (OFF-RAMP OR SLIPROAD), A DEDICATED EXIT LANE ON A FREEWAY, OR AT-GRADE ROAD (RIGHT OR LEFT TURN).
8. A CHANNELIZING LINE MAY BE USED AS AN EXTENSION OF A CONTINUITY LINE OR INSTEAD OF A PAINTED ISLAND TO CHANNELIZE TRAFFIC MOVEMENT WHERE SPACE IS LIMITED.
9. A LANE LINE, CONTINUITY LINE OR CHANNELIZING LINE SHALL NOT BE USED BETWEEN OPPOSING TRAFFIC MOVEMENTS.
10. THE WIDTHS OF LINES SHOWN ARE RECOMMENDATIONS ONLY (SEE LONGITUDINAL LINE COMBINATIONS).



GM4.2 REVERSIBLE FLOW ARROW / GM4.1 INFORMATION ARROW

DIMENSIONS (mm)

Operating Speed km/h	Typical Applications	a	a*	b	c	c*	d	e	f	g
30 - 40	City Centre	1250	2000	1250	450	400	50	750	500	250
50 - 60	Urban	2500	4000	1250	900	800	100	1500	500	250
70 - 90	Urban Arterial / Rural Expressway	4000	6400	1250	1440	1280	160	2400	500	250
100 - 120	Rural and Freeways	5000	8000	1250	1800	1600	200	3000	500	250



WM5

Area m²				
Marking	a	Area	a*	Area
WM1	4000	1.84		
	7500	6.00		
GM4.1/ GM4.2(a*)	1250	0.59	2000	1.05
	2500	1,17	4000	2.10
	4000	1.88	6400	3.36
	5000	2.35	8000	4.20
WM5	450	0.20		
	850	0.83		
	1350	2.15		
GM7	5500	6.90		


NOTES:

1. THIS DRAWING DETAILS A RANGE OF GENERAL WARNING OR GUIDANCE SYMBOLS. APPLICATION SHALL BE IN ACCORDANCE WITH THE SOUTH AFRICAN ROAD TRAFFIC SIGNS MANUAL.
2. MARKING WM5 - YIELD CONTROL AHEAD MAY BE REPEATED 1m FROM THE YIELD LINE




WM1

WM1 RAILWAY LEVEL CROSSING AHEAD



GM7 STOP



GM7

WM5 YIELD CONTROL AHEAD

DIMENSIONS (mm)

Operating Speed km/h	Typical Applications	Distance from Yield Line	a	b	c	d
30 - 40	City Centre	90m	450	250	100	1250
50 - 60	Urban	120m	850	450	150	2500
70 - 120	Rural	155m	1350	700	100	4000

DIMENSIONS (mm)

Typical Applications	a	b	c	d	e	f	g
Urban	4000	2500	1797	203	1135	115	200
Rural	7500	2500	3003	747	1042	208	400

REGULATORY/ WARNING/ GUIDANCE SYMBOLS

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	


BLOUBERG MUNICIPALITY


CONSULTANT:
SEBEGO, MALOKA & VILJOEN (PTY) LTD
CIVIL ENGINEERS
Reg.N°. 2006/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:
ROAD CARRIAGEWAY MARKINGS DETAILS
SHEET 1 OF 2

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-501	SHEET 1 OF 2
SMV PROJECT NUMBER	SCALE
	NTS
CONTRACT No.	DATE / REV No.
	2023.04.24 / B






APPLICATIONS

DIMENSIONS (mm)

Operating Speed km/h	Typical Applications	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r
30 - 40	City Centre	2500	600	350	450	884	200	417	1000	1700	250	550	1250	700	380	1450	58	30	29
50 - 90	Urban / Rural Expressway	4000	960	560	720	1406	320	666	1600	2720	400	880	2000	1120	608	2320	93	48	46
100 - 120	Rural and Freeways	5000	1200	700	900	1767	400	833	2000	3400	500	1100	2500	1400	760	2900	116	60	58
ALL	Special Applications	7500	1800	1050	1850	2651	600	1250	3000	5100	750	1650	3750	2100	1140	4350	174	90	87

All Operating Speeds and Applications	N	O	P	Q	R	S	T
	210	180	350	300	500	400	600




ARROW AREA / (m²)


a	RM8.1/RM8.5 WM7.1/WM7.5	RM8.2/RM8.4 WM7.2/WM7.4	RM8.3 WM7.3	RM8.6 WM7.6
2500	0.67	0.89	0.66	1.03
4000	1.14	1.43	1.06	1.68
5000	1.45	1.78	1.32	2.12
7500	2.23	2.66	1.98	3.20

NOTES: (MANDATORY DIRECTION ARROWS)

1. THESE ARROWS SHOULD BE USED IN LANES TO INDICATE THAT DRIVERS SHALL PROCEED ONLY IN THE DIRECTION OR DIRECTIONS SHOWN. THEY SHOULD ONLY BE USED IF THE JUNCTION CONCERNED REQUIRES TURNING MOVEMENT CONTROL BY LANE.
2. THE FINAL ARROW NEAREST THE POINT OF TURN OR STRAIGHT ON MOVEMENT SHALL BE YELLOW. ANY ARROWS MARKED IN ADVANCE OF THIS POINT TO WARN DRIVERS OF THE MANDATORY MOVEMENT AHEAD SHALL BE WHITE.
3. A MANDATORY OR WARNING DIRECTION ARROW SHALL NOT BE USED IN ADVANCE OF A WIDENING OF THE ROADWAY TO A GREATER NUMBER OF LANES. THIS SHALL BE INDICATED IF NECESSARY, BY USING FURCATION ARROWS.

MANDATORY DIRECTION ARROWS






APPLICATIONS

DIMENSIONS (mm)

Operating Speed km/h	Typical Applications	a	b	c	d	e	f	g	h	i	j
30 - 40	City Centre	2500	150	1000	2170	1141	268	761	1235	81	855
50 - 60	Urban / Roads	4000	240	1600	3472	1826	429	1218	1976	129	1367
70 - 90	Urban Arterial Roads/ Rural Expressways	5000	3000	2000	4340	2282	536	1522	2470	161	1709
100 - 120	Rural Roads and Freeways	7500	4500	3000	6510	3423	804	2283	3705	242	2564

All Operating Speeds and Applications	K	L	M	N	O	P	Q	R	S	T
	1700	1250	1100	210	180	921	329	300	188	161




NOTES: (FURCATION ARROWS)


1. THESE ARROWS MAY BE USED TO INDICATE THAT THE NUMBER OF LANES IS INCREASING AHEAD. ONLY ONE SET OF ARROWS SHOULD BE USED UNLESS A LEFT AND RIGHT TURN LANE ARE ADDED TO A MULTI-LANE ROADWAY AT THE SAME POINT WHERE TWO SETS MAY BE USED.
2. DIRECTION ARROWS AHEAD SHALL NOT BE USED TO INDICATE THE ADDITION OF LANES AHEAD.
3. AS A GENERAL RULE BIFURCATION ARROWS SHOULD BE LOCATED TWO TO THREE MARKING MODULES BEFORE THE START OF THE LANE GENERATING TAPER OR CURVE.

ARROW AREA / (m²)

a	GM3.1/GM3.3	GM3.2	GM3.4
2500	1.30	1.27	1.93
4000	2.07	2.04	3.09
5000	2.59	2.55	3.87
7500	3.89	3.82	5.80

FURCATION ARROWS





APPLICATIONS

DIMENSIONS (mm)

Operating Speed km/h	Typical Applications	a	b	c	d	e	f	g	h	i	j	k
30 - 40	City Centre	4000	2400	1600	3200	1271	847	227	855	1696	1277	1126
50 - 60	Urban / Roads	5000	3000	2000	4000	1589	1058	284	1069	2120	1596	1407
70 - 90	Urban Arterial Roads/ Rural Expressways	7500	4500	3000	6000	2384	1587	426	1603	3180	2394	2111
100 - 120	Rural Roads and Freeways	12000	7200	4800	9600	3814	2539	681	2566	5089	3830	3377


All Operating Speeds and Applications	M	N	O	P	Q	R	S	T	U	V
	300	210	180	1300	898	402	155	370	32	390

NOTES: (LANE REDUCTION ARROWS)


1. IT IS RECOMMENDED THAT THREE SETS OF ARROWS BE USED ON HIGH SPEED ROADS, SPACED AT FOUR MODULE INTERVALS BEFORE THE END OF THE LANE LINE. SINGLE ARROWS SETS MAY BE USED ON LOWER SPEED ROADS.
2. THE BENT ARROWS MAY BE USED IN ADDITION TO THE THREE-ARROW SETS ALONG THE LENGTH OF THE LANE REDUCTION TAPER.


ARROW AREA / (m²)

a	WM6.1/WM6.3	WM6.2
4000	2.08	2.06
5000	2.61	2.58
7500	3.92	3.88
12000	6.56	6.20



LANE REDUCTION ARROWS






LEGEND:
R = RED
W = WHITE
Y = YELLOW

APPLICATIONS


DIMENSIONS (mm)

Typical Applications	a	b	c	d	e	f	g	h	r	r*
Urban	3000	1941	83	976	1741	528	731	1206	5620	5820
Rural	4000	2588	111	1301	2321	704	975	1608	9900	10000

All Applications	H	I	J	K	L	M
	735	260	181	219	75	100 or 150



MARKING SPACING



NOTES: (BARRIER LINE AHEAD ARROWS)

1. THESE ARROWS SHOULD BE USED IN MULTIPLES OF THREE (AT LEAST) IN ADVANCE OF THE START OF A SECTION OF NO OVERTAKING LINE, NO CROSSING LINE OR PAINTED ISLAND WHEN SUCH BARRIER LINES REPLACE A DIVIDING LINE.
2. THE ARROWS MAY BE MARKED ON TOP OF EXISTING DIVIDING LINE MARKINGS (IF THE EXISTING LINE IS A CENTRELINE TO A 12m OR 7.2m MODULE THE POINT OF THE ARROW SHOULD BE LINED UP WITH THE FORWARD END OF THE LINE).
3. WHEN OVERTAKING SECTIONS ARE REGULARLY INTERSPERSED WITH NO OVERTAKING SECTIONS AND ARE SHORT IN LENGTH, MARKING WM8.2 MAY BE USED AT THE CENTRE OF THE OVERTAKING SECTION.

ARROW AREA / (m²)

a	Per Arrow
3000	0.62
4000	0.82

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº: 2005/018268/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
ROAD CARRIAGEWAY MARKINGS DETAILS
SHEET 2 OF 2

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-502	SHEET 2 OF 2
SMV PROJECT NUMBER	SCALE
	NTS
CONTRACT No.	DATE / REV No.
	2023.04.24 / B



TYPE 'A' FRAMEWORK PANELS


(FOR SIGN BOARDS WHERE H < 900mm




TYPE 'B' FRAMEWORK PANELS

(FOR SIGN BOARDS WHERE H > 900mm


TABLE 1				
POSITIONING OF ERECTION BRACKETS				
L (mm)	NUMBER OF SUPPORTS	H	A	A MAX
600 - 1500	1	R/W SIGNS	-	-
0 - 1500	1	⩽ 900	L/2	L/2
		> 900	L/2	L/2
1500 - 3600	2	⩽ 900	L/5	⩽ 800
		> 900	L/5	⩽ 700
3600 - 5400	3	⩽ 900	L/8	⩽ 800
		> 900	L/8	< 700
5400 - 7200	4	⩽ 900	L/11	< 800
		> 900	L/11	⩽ 700




POSITIONING OF SUPPORTS AND ERECTION BRACKETS



REINFORCEMENT FOR STANDARD ROAD SIGNS




END ELEVATION




FRONT ELEVATION


TYPICAL ERECTION BRACKETS




SIDE ELEVATION OF ROAD SIGN



FOUNDATION DETAIL




SIDE ELEVATION



SECTION A-A

(THROUGH D-SECTION STEEL POSTS)

ATTACHMENT DETAIL FOR SIGN BOARDS



TYPICAL WELDING DETAIL

TABLE 3	
BREAK-AWAY HOLES IN TIMBER POSTS	
NOMINAL ϕ OF POST	ϕ OF BREAK-AWAY HOLES
100-124mm	NONE
125-149mm	35mm
150-174mm	40mm
175-199mm	50mm
> 200mm	65mm
DISTANCE BETWEEN HOLES = 350mm	

NOTES:

1. DESIGN PARAMETERS
   WIND - 1:10 YR RETURN PERIOD (V=36m/s)
   SIGN HEIGHT : 5m (PRESSURE = 1.1kPa)
   PERMISSIBLE STEEL STRESS = 165MPa
2. FRAMEWORK : 25x25x2mm COMMERCIAL GRADE MILD STEEL
3. HORIZONTAL MEMBERS OF FRAMEWORK TO BE CONTINUOUS.
4. LARGE SIGN BOARDS TO BE MADE IN SECTIONS NOT EXCEEDING 3600mm IN LENGTH AND 900mm HIGH (TYPE 'A' PANELS) OR 3600mm IN LENGTH AND 1800mm HIGH (TYPE 'B' PANELS).
5. SECTIONS SHALL BE JOINED WITH GALVANIZED M10 BOLTS AND NUTS AT THE POSITIONS SHOWN.
6. ALL FRAMEWORK WELDS TO BE WELDED ALL ROUND. WELDS ON SIGN FACE SIDE TO BE GROUND TO PROVIDE SMOOTH SURFACE IN SAME PLANE AS FRAMEWORK.
7. FRAMEWORK TO BE PAINTED OR GALVANIZED AS PER PROJECT SPECIFICATIONS.
8. ERECTION BRACKETS SHALL BE WELDED TO ALL HORIZONTAL FRAMEWORK TUBES AT THE POSITION OF EACH SUPPORT, SUCH THAT THEY ARE VERTICALLY TRUE TO LINE.
9. MINIMUM LENGTH OF THE ERECTION BRACKETS TO R/W SIGNS: 100mm.
10. SIGN SUBSTRATE SHALL BE GALVANIZED MILD STEEL, FACTORY PREPAINTED WITH AN APPROVED SILICONE POLYESTER PAINT SYSTEM.

TABLE 2											
FOUNDATION AND SUPPORT SIZES											
SIGN HEIGHT H (mm)	L1 (mm)	FREE STANDING SUPPORTS				BRACED SUPPORTS					
		FOUNDATION		POSTS		POSTS			STAYS		
		BASE SIZE B (mm)	BASE DEPTH D (mm)	TIMBER POLE DIA (mm)	D-SECTION DIA x t (mm)	BASE SIZE B (mm)	BASE DEPTH D (mm)	TIMBER POLE DIA (mm)	BASE SIZE B (mm)	BASE DEPTH D (mm)	TIMBER POLE DIA (mm)
400-900	⩽2900	950	700	120	76 x 2	500	450	80	500	450	80
	2900-3400	1000	700	120	76 x 2	500	450	80	500	450	80
	3400-5600	1150	800	120	76 x 2	550	450	80	550	450	100
900-1200	⩽2900	1000	800	120	76 x 2	550	500	80	550	500	80
	2900-3400	1050	800	120	76 x 2	550	500	80	550	500	80
	3400-5600	1300	800	140	76 x 2	600	500	80	600	500	100
1200-1800	⩽2900	1200	800	140	76 x 2	700	500	80	550	500	80
	2900-3400	1300	800	140	100 x 4	700	500	80	700	500	80
	3400-5600	1450	900	160	100 x 4	700	500	80	700	600	120
1800-2400	⩽2900	1350	900	160	100 x 4	750	600	80	750	600	80
	2900-3400	1400	900	160	100 x 4	750	600	80	750	600	80
	3400-5600	1550	1000	180	100 x 4	750	600	80	750	600	120
2400-3000	⩽2900	1450	1000	180	100 x 4	850	600	100	850	600	80
	2900-3400	1500	1000	180	100 x 4	750	700	100	750	700	80
	3400-5600	1750	1000	200	100 x 4	800	700	100	800	700	120
3000-3600	⩽2900	1600	1000	180	100 x 4	850	700	100	850	700	80
	2900-3400	1650	1000	200	100 x 4	850	700	100	850	700	100
	3400-5600	1900	1000	220	100 x 4	900	700	120	900	700	120
3600-4200	⩽2900	1700	1000	180	100 x 4	900	700	120	900	700	80
	2900-3400	1750	1000	200	100 x 4	900	700	120	900	700	100
	3400-5600	2000	1000	220	100 x 4	950	700	120	950	700	120
4200-4800	⩽2900	1850	1000	220	100 x 4	950	700	120	950	700	100
	2900-3400	1900	1000	220	100 x 4	1000	700	140	1000	700	100
	3400-5600	2300	1000	220	100 x 4	1150	700	140	1150	700	140
SINGLE POST REGULATORY AND WARNING SIGNS											
4600-1500	⩽3000	950	700	-	76 x 2	USE ONLY FREE STANDING SUPPORTS					

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg N°. 2004/014586/07
SUITE 228
POSTNET X9307
POLOKWANE
0700
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
ROAD SIGNS - TYPICAL MANUFACTURING AND ERECTION DETAILS

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-503	SHEET 1 OF 1
SMV PROJECT NUMBER	SCALE
	NTS
CONTRACT No.	DATE / REV No.
	2023.04.24 / B



TYPICAL GUARDRAIL SECTION

SCALE 1:5




SECTION THROUGH GUARDRAIL

SCALE 1:2


NOTE:

1. GUARDRAILS WILL ONLY BE PLACED WHERE REQUIRED BY THE ENGINEER.
2. ALL GUARDRAILS MUST BE GALVANIZED AS SPECIFIED (NOT PAINTED).



ELEVATION OF GUARDRAIL

SCALE 1:5



DETAIL A: FRONT ELEVATION NORMAL SPACING OF POSTS

SCALE 1:5

NOTES ON ERECTION DETAILS

1. THE HOLES FOR TIMBER POSTS SHALL BE OF SUFFICIENT SIZE TO ALLOW PROPER SETTING OF THE POSTS AND SUFFICIENT ROOM FOR BACKFILLING.
2. AT LEAST 1,0m OF POST SHALL BE EMBEDDED IN THE GROUND
3. HOLES FOR TIMBER POSTS SHALL BE SPACED TO SUIT STANDARD LENGTHS OF GUARDRAILS SUPPLIED.
4. HOLES SHALL BE BACKFILLED WITH 12:1 SOIL : CEMENT MIXTURE AT OPTIMUM MOISTURE CONTENT IN COMPACTED LAYERS NOT EXCEEDING 100mm.

GUARDRAIL WARRANTS

1. WHERE THE FILL IS HIGHER THAN 4,0m FOR SURFACED ROADS, AND 6,0m FOR GRAVEL ROADS.
2. WHERE WATER NEXT TO THE ROAD FORMATION IS DEEPER THAN 1,5m.
3. AT ALL BRIDGES WITH BALUSTRADES.
4. ON THE OUTSIDE OF CURVES WITH RADII LESS THAN 200m ONLY WHEN THE ROAD IS IN FILL.
5. WHERE OBSTRUCTIONS ARE LESS THAN 1,0m FROM THE SHOULDER BREAKPOINT.
6. WHERE AN OBSTRUCTION APPEARS TO BE MORE DANGEROUS THAN A GUARDRAIL WOULD BE.

THESE RULES ARE TO BE APPLIED WITH DISCRETION AND THE POSITION OF ALL GUARDRAILS MUST BE CONFIRMED ON SITE BY THE ENGINEER PRIOR TO THE ERECTION THEREOF.

SPECIFICATIONS

1.BOLT:
HIGH TENSILE STEEL 16mm Ø

2.WASHERS:
3mm THICK

3.SPACER BLOCK:
PINE OR GUM, PRESSURE IMPREGNATED WITH CREOSOTE WHICH COMPLIES WITH SABS 538 OR 539


4.POSTS:
150mm Ø MIN - 230mm Ø MAX, PINE OR GUM, PRESSURE IMPREGNATED WITH CREOSOTE WHICH COMPLIES WITH SABS 538 OR SABS 539.

5.GALVANIZING:
GUARDRAILS:SABS 763:TYPE A1 ARTICLES. BOLTS AND WASHERS: SABS 763 TYPE C1 ARTICLES

6.TIMBER POSTS:
POSTS SHALL COMPLY WITH THE REQUIREMENTS OF SABS AND SHALL CARRY THE SABS MARK.


7.CREOSOTE TREATMENT:
TIMBER POSTS AND SPACER BLOCKS SHALL BE TREATED IN ACCORDANCE WITH SABS 05 WITH CREOSOTE WHICH COMPLIES WITH SABS 538 OR 539F.


8.REFLECTIVE PLATES:
THE OUTER SURFACES SHALL BE COATED WITH ENGINEERING GRADE RETRO-REFLECTIVE MATERIAL WHICH COMPLIES WITH THE PROVISIONS OF CKS 191 IN THE COLOURS SHOWN ON THIS DRAWING.



PLAN


SCALE 1 : 5






DETAIL B: FRONT ELEVATION HALF SPACING OF POSTS

SCALE 1:5




BASEPLATE SHOWN UNCRIMPED

SECTION PLAN




DETAIL OF BASEPLATE




DETAIL OF STEEL GUARDRAIL POST

SCALE 1:10




SECTION C - C ON OUTSIDE OF HORIZONTAL CURVE

nts




TYPICAL BOLTS

SCALE 1:1



FRONT ELEVATION : TYPE D1 (A)

TRAFFIC DIRECTION




FRONT ELEVATION : TYPE D1 (B)

NOTE:

V-SHAPED REFLECTIVE PLATES ATTACHED TO EACH ALTERNATIVE POST - 7,62m c/c.

DETAIL OF GUARDRAIL REFLECTIVE PLATES



HALF-SPACING OF GUARDRAIL POSTS

NORMAL SPACING OF GUARDRAIL POSTS

SPACING OF POSTS AND POSITION OF REFLECTIVE PLATES

SCALE 1:25

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SMV CIVIL ENGINEERS (PTY)LTD
SEBEGO, MALOKA & VILJOEN
Reg.N°. 2006/018585/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:
LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:
GUARD RAIL ELEMENTS & MOUNTING DETAILS

DRAWING NUMBER	SHEET No.
SMV-LET-PIC-504	SHEET 1 OF 1
SMV PROJECT NUMBER	SCALE
	AS SHOWN
CONTRACT No.	DATE / REV No.
	2023.04.24 / B




TYPICAL ROAD CROSS SECTION WITHOUT SIDEWALKS

(AS DIRECTED BY THE ENGINEER ON SITE)




TYPICAL ROAD CROSS SECTION WITH SIDEWALKS

CH 0+060 TO CH 5+843



TYPICAL ROAD PAVEMENT SCHEDULE

CH 0+060 TO CH 5+843




TYPICAL ROAD PAVEMENT SCHEDULE

CH 0+000 TO CH 0+060




TYPICAL WALKWAY PAVEMENT SCHEDULE


CH 0+060 TO CH 5+843




STANDARD FIG 8(c) PRECAST MOUNTABLE KERB DETAILS



STANDARD FIG 7 PRECAST SEMI-MOUNTABLE KERB



EDGE BEAM DETAIL



STANDARD FIG 10 KERB DETAILS

MARK	DATE	INITIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.24	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	PM
DRAWN BY	CDN
CHECKED BY	

BLOUBERG MUNICIPALITY


CONSULTANT:
SEBEGO, MALOKA & VILJOEN (PTY)LTD
Reg.N°. 2006/018868/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za


ARCHITECT:


PROJECT NAME: **LETHALENG TO PICKUM ROAD UPGRADING**


DRAWING TITLE: **TYPICAL ROAD CROSS SECTION, PAVEMENT SCHEDULE & KERBING DETAILS**


DRAWING NUMBER	SMV-LET-PIC-600
SHEET No.	SHEET 1 OF 1
SMV PROJECT NUMBER	
SCALE	AS SHOWN
CONTRACT No.	
DATE	2023.04.24
REV No.	B






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015068/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelat@scon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 0,000 TO KM 0,580


DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-601	SHEET 1 OF 10	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015068/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelat@scon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 0,600 TO KM 1,180


DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-602	SHEET 2 OF 10	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015068/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelat@scon.co.za

ARCHITECT:

PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING

DRAWING TITLE:

ROAD CROSS SECTIONS:

KM 1,200 TO KM 1,780

DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-603	SHEET 3 OF 10	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	



MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT: BLOUBERG MUNICIPALITY


CONSULTANT: SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015058/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za


ARCHITECT:


PROJECT NAME: **LETHALENG TO PICKUM ROAD UPGRADING**


DRAWING TITLE: **ROAD CROSS SECTIONS: KM 1,800 TO KM 2,380**


DRAWING NUMBER	SMV-LET-PIC-604	SHEET No.	SHEET 4 OF 10
PAPER SIZE	A0		
SMV PROJECT NUMBER		SCALE	AS SHOWN
CONTRACT No.		DATE	2023.04.18
REV No.	B		






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015068/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelat@scon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 2,400 TO KM 2,980


DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-605	SHEET 5 OF 10	A0	
SMV PROJECT NUMBER	SCALE	AS SHOWN	
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SEBEGO MALOKA & VILJOEN (PTY) LTD
CIVIL ENGINEERS
Reg.Nº. 2006/015058/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 3,000 TO KM 3,580


DRAWING NUMBER	SHEET No.	PAPER SIZE
SMV-LET-PIC-606	SHEET 6 OF 10	A0
SMV PROJECT NUMBER	SCALE	
	AS SHOWN	
CONTRACT No.	DATE	REV No.
	2023.04.18	B






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015058/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 3,600 TO KM 4,180


DRAWING NUMBER	SMV-LET-PIC-607	SHEET No.	SHEET 7 OF 10
PAPER SIZE	A0		
SMV PROJECT NUMBER		SCALE	AS SHOWN
CONTRACT No.		DATE	2023.04.18
REV No.	B		






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015068/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelat@icon.co.za

ARCHITECT:


PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:
KM 4,200 TO KM 4,780


DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-608	SHEET 8 OF 10	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	






















































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT:

BLOUBERG MUNICIPALITY

CONSULTANT:

SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015058/07

SUITE 228
POSTNET X9307
POLOKWANE
0070

Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME:


LETHALENG TO PICKUM ROAD UPGRADING


DRAWING TITLE:


ROAD CROSS SECTIONS:


KM 4,800 TO KM 5,380


DRAWING NUMBER	SHEET No.	PAPER SIZE	
SMV-LET-PIC-609	SHEET 9 OF 10	A0	
SMV PROJECT NUMBER	SCALE		
	AS SHOWN		
CONTRACT No.	DATE	REV No.	
	2023.04.18	B	




































































MARK	DATE	INTIALS	REVISION
B	2023.05.12	KM	ISSUED FOR TENDER
A	2023.04.18	KM	PRELIMINARY DESIGN

NOTES:

1. DO NOT SCALE OFF THIS DRAWING

DESIGNED BY	KM
CHECKED BY	KM
DRAWN BY	CDN
CHECKED BY	

CLIENT: BLOUBERG MUNICIPALITY

CONSULTANT: SMV CIVIL ENGINEERS (PTY) LTD
SEBEGO, MALOKA & VILJOEN
Reg.Nº. 2006/015058/07
SUITE 228
POSTNET X9307
POLOKWANE
0070
Tel: 015 - 291 5376/7
Fax: 015 - 291 5379
Email: phelad@icon.co.za

ARCHITECT:

PROJECT NAME: **LETHALENG TO PICKUM ROAD UPGRADING**

DRAWING TITLE: **ROAD CROSS SECTIONS: KM 5,400 TO KM 5,843**

DRAWING NUMBER	SHEET No.	PAPER SIZE
SMV-LET-PIC-610	SHEET 10 OF 10	A0
SMV PROJECT NUMBER	SCALE	
	AS SHOWN	
CONTRACT No.	DATE	REV No.
	2023.04.18	B